

PP

► HI828

High MFR Homo PP for Injection Molding

Description

HI828 is high MFR homo PP for injection molding application. It shows an easy processability, high rigidity and excellent dimensional stability. **HI828** offers the productivity enhancement by cycle time reduction and meet the demand of Food application.

Characteristics

- ▶ High flowability; easy injection processing, thin wall products
- ► High rigidity; small deformation under load
- ▶ High crystallinity & dimensional stability; cycle time reduction

Applications

► Thin wall food container, Houseware

Physical Properties

Typical Properties	Method (ASTM)	Unit	HI828
Melt flow index	D1238	g/10min	45
Density	D1505	g/cm ³	0.91
Tensile strength at yield	D638	kg/cm ²	410
Elongation at break	D638	%	>300
Flexural modulus	D790	kg/cm ²	20,000
Izod impact strength 23 °C	D256	kgcm/cm	2.7
Rockwell hardness	D785	R-scale	107
Heat distortion temp.	D648	$^{\circ}$	130

^{*} Data shown above are representative values for reference purposes only, and not to be construed as specifications.

^{*} Data performed by or on behalf of <u>www.cn-plas.com</u> Hanwha Total



Food Contact Application

- ▶ Hanwha Total HI828 meets the FDA requirements in the Code of Federal Regulations in 21 CFR 177.1520 for food contact.
- ▶ In case you might need additional technical or regulatory information, please contact Hanwha Total Polymer Technical Service Team.

	Co	nta	cts
•	CU	ııta	CLO

▶ Product Information & Technical Services

Disclaimer

This www.cn-plas.com document is copyright of Hanwha Total petrochemicals Co., Ltd. Any and all information and the values in this document are typical properties for reference, not to be confused with, or regarded as specification. Customers are responsible for determining whether our products and information are suitable for their particular purpose and for ensuring that Customer's location and handling practices are in compliance with laws and regulations. HANWHA TOTAL assumes no obligation or liability for the information in this document. NO EXPRESS WARRANTIES ARE

GIVEN EXCEPT FOR ANY APPLICABLE WRITTEN WARRANTIES SPECIFICALLY PROVIDED BY HANWHA TOTAL. ALL IMPLIED WARRANTIES INCLUDING THOSE OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED. HANWHA TOTAL is entitled to alter, change or modify any of the content herein at any time without prior notice, but not under any duty to do so.

LTE31315